

# 1275 SERIES LARGE CAPACITY DUAL HOSE REELS

**COXREELS® 1275 Series “Dual Hose” hand crank or motorized hose reels are designed for large capacity applications.** This series features dual plumbing with two swivel inlets and two low profile outlets that compliment the open drum slot and provide a non-crimping, flat smooth hose wrap. The industry preferred one piece all welded “A” frame design adds rigidity and strength while the positive gear drive rewind assures consistent trouble-free performance.

## 1275 SERIES MODELS

MODEL	LESS HOSE										SIZE INDEX
	STANDARD CAP			OPTIONAL CAP. Reducer required			INLET SWIVEL & OUTLET RISER	PSI	APRX. LBS.		
	I.D.	O.D.	FT.	I.D.	O.D.	FT.					
<b>1275-4-50-X</b>	1/2"	7/8"	2/50	3/8"	3/4"	2/70	1/2" F NPT	3,000	40		<b>1</b>
<b>1275-4-100-X</b>	1/2"	7/8"	2/100	3/8"	3/4"	2/140	1/2" F NPT	3,000	42		<b>2</b>
<b>1275-4-150-X</b>	1/2"	7/8"	2/150	3/8"	3/4"	2/200	1/2" F NPT	3,000	47		<b>3</b>
<b>1275-4-200-X</b>	1/2"	7/8"	2/200	3/8"	3/4"	2/300	1/2" F NPT	3,000	56		<b>4</b>
<b>1275-6-50-X</b>	1"	1 7/16"	2/50	3/4"	1 1/4"	2/60	1" F NPT	3,000	63		<b>5</b>
<b>1275-6-75-X</b>	1"	1 7/16"	2/75	3/4"	1 1/4"	2/110	1" F NPT	3,000	68		<b>6</b>
<b>1275-6-100-X</b>	1"	1 7/16"	2/100	3/4"	1 1/4"	2/155	1" F NPT	3,000	74		<b>7</b>
<b>1275-6-150-X</b>	1"	1 7/16"	2/150	3/4"	1 1/4"	2/200	1" F NPT	3,000	88		<b>8</b>



1275-E Series

### 1275 SERIES :: REEL SPECIFICATIONS

#### SWIVEL

- Two external fluid paths with machined from solid brass 90° full-flow NPT swivel inlets (one on each side of the reel)
- Swivel Seals: NITRILE
- Swivel O-ring seals supported by Teflon spacers
- Electroless nickel plated steel swivel on 1" models

#### DESIGN & STRUCTURE

- All welded steel “A” frame construction for superior reel structure
- Two low profile outlet risers & open drum slot design for dual hose applications
- Permanently lubricated self-aligning pillow block bearings for trouble-free & smooth rotation

#### RETRACTION

- Reliable direct gear drive on motor driven models - **NO CHAIN**
- Bevel gear hand crank with removable handle for compact storage
- See Motor Options Chart

#### SIGNATURE FEATURES

- Professional grade heavy duty steel construction
- Durable proprietary CPC™ powder coat process
- Rolled edges & ribbed discs provide strength & safety
- Leading 2-year manufacturer's limited warranty
- Made in the U.S.A. - Sold & Supported Worldwide

#### POSSIBLE FIELDS OF APPLICATION

- Twin Agent Applications
- Fire Suppression
- Offshore Oil Rigs
- Shipyard & Port Operations
- Hydraulic
- Mining Operations
- Aircraft Maintenance
- Petroleum Production Fields

#### ACCESSORIZE YOUR REEL :: PG 50

- O-Rings & Swivels
- Roller Brackets
- Hoses
- Assorted Reel Accessories

#### - SUFFIX “X” OPTIONS

When ordering, substitute the “X” with selection below. Add 5 lbs to ship weight if reel is crated.

SUFFIX	TYPE	DESCRIPTION	ADD ON APRX. LBS*
<b>A</b>	AIR - #4 GAST	COMP. AIR MOTOR	8
<b>E</b>	ELEC. - 12V DC	1/3 HP REV. REV. TYPE	13
<b>EF</b>	ELEC. - 24V DC	1/3 HP REV. REV. TYPE	13
<b>EB</b>	ELEC. - 24V DC	1/2 HP REV. REV. TYPE	26
<b>ED</b>	ELEC. - EXPL. PRF. - 12V DC	1/2 HP REV. REV. TYPE	26
<b>EA</b>	ELEC. - EXPL. PRF. - 115V	1/2 HP REV., AC REV. TYPE	26
<b>H</b>	HYDRAULIC	END PORTED 9/16-18 UNF REV.	6
<b>C</b>	FRONT HAND CRANK	BEVEL GEARED CRANK	3

#### REEL DIMENSIONS

Technical Data Sheets Available On Website

SIZE INDEX	W			H		L	X	Y		Ø	Dw
	CRANK	ELEC.	AIR / HYD.	CRANK	ELEC.			CRANK	ELEC.		
<b>1</b>	18 7/8"	22 5/8"	19 7/8"	18 5/8"	19 1/8"	17 5/8"	13 3/8"	15 3/8"	16"	6 1/4"	8"
<b>2</b>	22 7/8"	26 5/8"	23 7/8"	18 5/8"	19 1/8"	17 5/8"	17 3/8"	15 3/8"	16"	6 1/4"	12"
<b>3</b>	28 7/8"	32 5/8"	29 7/8"	18 5/8"	19 1/8"	17 5/8"	23 3/8"	15 3/8"	16"	6 1/4"	18"
<b>4</b>	34 7/8"	38 5/8"	35 7/8"	18 5/8"	19 1/8"	17 5/8"	29 3/8"	15 3/8"	16"	6 1/4"	24"
<b>5</b>	-	30 5/8"	27 3/4"	22 7/8"	22 7/8"	20"	19"	18 7/8"	18 7/8"	10 1/2"	13 1/2"
<b>6</b>	-	30 5/8"	27 3/4"	26 1/8"	26 1/8"	24"	19"	20 3/8"	20 3/8"	10 1/2"	13 1/2"
<b>7</b>	-	37"	34 1/4"	26 1/8"	26 1/8"	24"	25 1/2"	20 3/8"	20 3/8"	10 1/2"	20"
<b>8</b>	-	37"	34 1/4"	30 1/16"	30 1/16"	28"	25 1/2"	22 9/16"	22 9/16"	10 1/2"	20"

